

**BUREAU OF BROADCAST SERVICES**  
**4<sup>TH</sup> Floor, Media Center Building,**  
**Visayas Avenue, Quezon City**

**CANVASS FORM**

Date: \_\_\_\_\_

PR Number: 2022-04-0187

Gentlemen: Please quote your government price/s for the article/s listed hereunder:

Item No.	Qty	Unit	Articles	Approved Total ABC	Amount
1	1	Lot	<b>Rack Mounted Server, Rack, and Accessories</b>	<b>P678,800.00</b>	
	2	units	<b>BRANDED 1U RACK SERVER</b> Specification: <b>Processor</b> Intel Xeon E-2234 3.6 GHz, 8M cache, 4C/8T, turbo (71W) <b>Cache Memory</b> 8M Cache <b>Memory</b> 16GB 2666MT/s DDR4 ECC UDIMM <b>Network Controller</b> On-Board Broadcom 5720 Dual Port 1Gb LOM <b>Storage Controller</b> RAID Controller <b>Hard Drive</b> 1TB 7.2K RPM SATA 6Gbps 3.5" Hot-Plug Hard Drive, 13G (max 4 HDD) <b>Optical Drive</b> DVD+/-RW, SATA, Internal <b>Power Supply</b> Single, Hot-Plug Power Supply, 350W <b>Form Factor</b> 1U Rack Server, Sliding Rails w/ Cable Management Arm <b>Warranty</b> 3 Yrs Pro Support Next Business Day Onsite Service <b>Mouse</b> Optical Mouse <b>Keyboard</b> Multimedia Keyboard (English) Black <b>Monitor</b> 18.5" Widescreen Monitor with LED <b>OS</b> Windows Server 2019, Standard, ROK, 16CORE <b>Secondary Power Supply</b> 350W Single Hot-Plug Power Supply, Cuskit		
	2	units	<b>2TB 7.2K RPM NLSAS 12Gbps 512n 3.5" Hot-Plug Hard Drive, CK</b>		
	1	unit	<b>SERVER RACK – 24RU (FREE STANDING)</b> ➤ H=600mm x D=1070mm ➤ H=1198.5mm ➤ 19" Standard opening systems ➤ Framing & paneling gauge#16 ➤ Adjustable mounting railings ➤ Perforated front door w/ swing handle lock (single door) ➤ Perforated back door w/ swing handle lock (split type) ➤ Detachable side panels w/ push lock & ventilation ➤ w/ 2pcs. Monitor tray ➤ w/ vertical power strip 8 outlets, 3 prong, 220v-20amp-fuse capacity w/ 1 meter power cord ➤ w/ 4 pcs. Exhaust fan @ the top panel ➤ w/ vertical cable manager @ the back (ring type) ➤ w/ 30 pcs. Cage nuts & screws ➤ w/ caster wheels & leveling feet ➤ black (powder coated) ➤ bolted type		
	1	unit	<b>RACKMOUNT UPS 2200V LCD RM 2U 230V, with RJ45 Serial Port, Network Capability</b> ➤ <b>Output power capacity</b> 1.98kWatts / 2.2kVA ➤ <b>Rack Height</b> 2U ➤ <b>Output Connections :</b> • (1) IEC 320 C19 (Battery Backup) • (8) IEC 320 C13 (Battery Backup) • (3) IEC Jumpers (Battery Backup) ➤ <b>Nominal Input /Output Voltage</b> 230V ➤ <b>Input Connections</b> BS1363A British, IEC 320 C20, Schuko CEE 7 / EU1-16P ➤ <b>Operating Temperature</b> 0 - 40 °C ➤ <b>Operating Relative Humidity</b> 0 - 95 % ➤ <b>Operating Elevation</b> 0 - 3048meters ➤ <b>Storage Temperature</b> -15 - 45 °C ➤ <b>Storage Relative Humidity</b> 0 - 95 % ➤ <b>Storage Elevation</b> 0 - 15240meters ➤ <b>Audible noise at 1 meter from surface of unit</b> 55.0dBA		

